



Thermo-Sil NPTM HS Silicone Roof Coating

SAFETY DATA SHEET

1. Identification

Product Identifier: Thermo-Sil NPTM HS Silicone

Other means of identification

Synonyms: Mastic Coating

Recommended use and restriction on use

Recommended use: Protection of construction materials

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information : Icynene-Lapolla
15402 Vantage Pkwy East, Suite 322
Houston, TX 77032

Telephone/General Information : +1 281 219 4100 , (877) 636-2648

Contact Person : sds@icynene-lapolla.com

Emergency Telephone Number Supplier : CARECHEM (866) 928-0789

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 4

Health Hazards

Carcinogenicity Category 1A

Label Elements

Hazard Symbol:

Thermo-Sil NPTM HS Silicone Roof Coating



Signal Word: Danger

Hazard Statement: H227; Combustible liquid.
H350; May cause cancer.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: If exposed or concerned: Get medical advice/attention. In case of fire: Stop leak if safe to do so.

Storage: Store in well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: None.

3. Composition/information on ingredients
--



Thermo-Sil NPTM HS Silicone Roof Coating

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
(1) Calcium Carbonate	471-34-1	20 - <50%	# This substance has workplace exposure limit(s).
(1) TITANIUM DIOXIDE	13463-67-7	1 - <5%	# This substance has workplace exposure limit(s).
Titanium, Bis(ethyl acetoacetato)-diispropoxy	27858-32-8	1 - <5%	No data available.
Octadecanoic acid	57-11-4	1 - <5%	# This substance has workplace exposure limit(s).
(1) QUARTZ	14808-60-7	0.1 - <1%	# This substance has workplace exposure limit(s).

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

General information:	No action shall be taken involving any personal risk or without suitable training.
Ingestion:	If swallowed, do NOT induce vomiting. Give a glass of water.
Inhalation:	If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.
Skin Contact:	Wash contaminated clothing before reuse. In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention.
Eye contact:	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Most important symptoms/effects, acute and delayed	
Symptoms:	No data available.
Hazards:	No data available.



Thermo-Sil NPTM HS Silicone Roof Coating

Indication of immediate medical attention and special treatment needed

Treatment: Treatment is symptomatic and supportive.

5. Fire-fighting measures

General Fire Hazards: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use standard firefighting procedures and consider the hazards of other involved materials.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: In case of fire, carbon monoxide and carbon dioxide may be formed. Acute overexposure to the products of combustion may result in irritation of the respiratory tract. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Combustible This product or a component thereof can flow along surface to reach a distant ignition source and flash back. Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Product releases methanol during application and curing. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Avoid inhalation of vapors and spray mists. Keep container closed. Keep out of reach of children. See Section 8 of the SDS for Personal Protective Equipment.

Methods and material for containment and cleaning up: Wear proper protective equipment as specified in the protective equipment section. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for disposal. Warn other workers of spill. Keep unauthorized personnel away.



Thermo-Sil NPTM HS Silicone Roof Coating

Notification Procedures: Caution: Contaminated surfaces may be slippery. See Section 8 of the SDS for Personal Protective Equipment.

Environmental Precautions: Do not allow runoff to sewer, waterway or ground.

7. Handling and storage

Precautions for safe handling: Sensitivity to static discharge is expected; material has a flash point below 200 F. Do not get in eyes, on skin, on clothing. Do not taste or swallow. Use only in well-ventilated areas. See Section 8 of the SDS for Personal Protective Equipment.

Conditions for safe storage, including any incompatibilities: Keep container tightly closed. Recommended storage in original container below 30°C (85°F).

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
(1) Calcium Carbonate - Total	REL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
(1) Calcium Carbonate - Respirable.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
(1) Calcium Carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
(1) Calcium Carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
(1) Calcium Carbonate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
(1) Calcium Carbonate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
(1) TITANIUM DIOXIDE	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
(1) TITANIUM DIOXIDE - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Octadecanoic acid	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
(1) QUARTZ - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
(1) QUARTZ - Respirable dust.	REL	0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
(1) QUARTZ - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
(1) QUARTZ	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)



Thermo-Sil NPTM HS Silicone Roof Coating

Appropriate Engineering Controls Eye washes and showers for emergency use.

Individual protection measures, such as personal protective equipment

General information: Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

Eye/face protection: Monogoggles

Skin Protection

Hand Protection: Chemical resistant gloves

Other: Wear suitable protective clothing and eye/face protection.

Respiratory Protection: If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

Hygiene measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties
--

Appearance

Physical state: liquid
Form: liquid
Color: Various
Odor: Alcohol
Odor threshold: No data available.
pH: not applicable
Melting point/freezing point: not applicable
Initial boiling point and boiling range: No data available.
Flash Point: 70 °C
Evaporation rate: No data available.
Flammability (solid, gas): No data available.
Upper/lower limit on flammability or explosive limits
Flammability limit - upper (%): No data available.



Thermo-Sil NPTM HS Silicone Roof Coating

Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Heat of combustion:	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Density:	No data available.
Relative density:	1.3
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water) Log Pow:	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
SADT:	No data available.
Viscosity, dynamic:	No data available.
Viscosity, kinematic:	No data available.
VOC:	24 g/l

10. Stability and reactivity

Reactivity:	No dangerous reaction if used as recommended.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerisation does not occur.
Conditions to avoid:	Keep away from heat. Keep away from sources of ignition - No smoking.
Incompatible Materials:	Oxidizing agents. Water.
Hazardous Decomposition Products:	Carbon oxides Oxides of silicon. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

11. Toxicological information

Information on likely routes of exposure

Ingestion: No data available.

Inhalation: No data available.



Thermo-Sil NPTM HS Silicone Roof Coating

Skin Contact: No data available.

Eye contact: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 173,611.11 mg/kg

Specified substance(s):

(1) TITANIUM DIOXIDE LD 50 (Rat): > 10,000 mg/kg

Octadecanoic acid LD 50 (Rat, No data available.): > 2,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

(1) TITANIUM DIOXIDE LD 50 (Rabbit): > 10,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

(1) TITANIUM DIOXIDE LC50 (Rat): > 6.8 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.



Thermo-Sil NPTM HS Silicone Roof Coating

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

(1) QUARTZ Overall evaluation: 1. Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

(1) QUARTZ Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.



Thermo-Sil NPTM HS Silicone Roof Coating

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE LC0 (Leuciscus idus, 48 h): > 1,000 mg/l

Octadecanoic acid LC0 (Brachydanio rerio, 96 h): > 100 mg/l
LC0 (Leuciscus idus, 96 h): > 100 mg/l

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Octadecanoic acid LC0 (Brachydanio rerio, 4 d): > 100 mg/l
LC0 (Leuciscus idus, 4 d): > 100 mg/l

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE 0 %

BOD/COD Ratio

Product: No data available.



Thermo-Sil NPTM HS Silicone Roof Coating

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

(1) Calcium Carbonate	No data available.
(1) TITANIUM DIOXIDE	No data available.
Titanium, Bis(ethyl acetoacetato)-diispropoxy	No data available.
Octadecanoic acid	No data available.
(1) QUARTZ	No data available.

Other adverse effects: No data available.

13. Disposal considerations

General information: The generation of waste should be avoided or minimized wherever possible. Do not discharge into drains, water courses or onto the ground. See Section 8 for information on appropriate personal protective equipment.

Disposal instructions: Disposal should be made in accordance with federal, state and local regulations.

Contaminated Packaging: Dispose of as unused product.

14. Transport information

DOT

UN Number:	NA 1993
UN Proper Shipping Name:	Combustible liquid, n.o.s.(Decamethylcyclopentasiloxane)
Transport Hazard Class(es)	
Class:	CBL
Label(s):	NONE
Packing Group:	III
Marine Pollutant:	No

IMDG

Not regulated.



Thermo-Sil NPTM HS Silicone Roof Coating

IATA

Not regulated.

Special precautions for user:

This product is Combustible as defined by the US Department of Transportation (DOT). It is regulated for transport in the US in container > 119 gallons. The product is not regulated for transport by the IATA, ADR/RID, ADNR or the IMDG regulations.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
(1) Calcium Carbonate	10000 lbs
(1) TITANIUM DIOXIDE	10000 lbs
Titanium, Bis(ethyl acetoacetato)-diisopropoxy	10000 lbs
Octadecanoic acid	10000 lbs
(1) QUARTZ	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.



Thermo-Sil NPTM HS Silicone Roof Coating

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

- | | |
|----------------------|---|
| (1) TITANIUM DIOXIDE | Carcinogenic. |
| (1) QUARTZ | Carcinogenic. |
| Methanol | Maximum Allowable Dose Level
(MADL): 47000 µg/day.
Developmental toxin. |

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Siloxanes and Silicones, di-Me hydroxy terminated

(1) Calcium Carbonate

Decamethylcyclopentasiloxane

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl) -, reaction products with ammonia, octamethylcyclotetrasiloxane and silica

(1) TITANIUM DIOXIDE

(1) QUARTZ

US. Massachusetts RTK - Substance List

Chemical Identity

(1) Calcium Carbonate

(1) TITANIUM DIOXIDE

(1) QUARTZ

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

(1) Calcium Carbonate

(1) TITANIUM DIOXIDE

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.



Thermo-Sil NPTM HS Silicone Roof Coating

Inventory Status:

Australia AICS:	y (positive listing)	Remarks: None.
EU EINECS List:	y (positive listing)	Remarks: None.
Japan (ENCS) List:	y (positive listing)	Remarks: None.
China Inventory of Existing Chemical Substances:	y (positive listing)	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	y (positive listing)	Remarks: None.
Canada DSL Inventory List:	y (positive listing)	Remarks: None.
Canada NDSL Inventory:	n (Negative listing)	Remarks: None.
Philippines PICCS:	y (positive listing)	Remarks: None.
US TSCA Inventory:	y (positive listing)	Remarks: On TSCA Inventory
Taiwan. Taiwan inventory (CSNN):	y (positive listing)	Remarks: None.

16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	*	0
Flammability		2
Physical Hazards		1
PERSONAL PROTECTION		

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 04/21/2017
Revision Date: No data available.
Version #: 3.3
Further Information: No data available.



Thermo-Sil NPTM HS Silicone Roof Coating

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Icynene-Lapolla products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.